



ELEKTRO AGREGATI - GENERATING SETS

MOTORJI MITSUBISHI - ENGINES MITSUBISHI
VODNO HLAJENI MOTORJI - WATER COOLED ENGINES

50Hz / 1500 o/min - 230/400V

Engine type	Prime power		Stand-by power		DIESEL engine		Generating set type				Generating set type				Generating set type				Fuel			
	kVA	kW	kVA	kW	Electroni c regulatio	Emission certification	MISM1-Open version				MISM2-Water-proof canopy				MISM3-Super silent canopy				Consumption			Tank capacity (liter)
							Dimensions				Dimensions				Dimensions				100% (l/h)	75% (l/h)	50% (l/h)	
	L(mm)	W(mm)	H(mm)	m(kg)	L(mm)	W(mm)	H(mm)	m(kg)	L(mm)	W(mm)	H(mm)	m(kg)	100% (l/h)	75% (l/h)	50% (l/h)							
S6R-PTA	580	464	638	510	Standard	TA Luft	3500	1500	2200	5600	4020	1520	2550	6300	4420	1520	2550	6600	120	90	66	1000
S6R2-PTA	675	540	743	594	Standard	TA Luft	3500	1500	2200	5800	4020	1520	2550	6500	4420	1520	2550	6800	140	105	77	1000
S12A2-PTA	770	616	847	678	Standard	TA Luft	3500	1500	2200	6500	4020	1520	2550	7200	4420	1520	2550	7500	167	125	92	1000
S12H-PTA	1030	824	1133	906	Standard	TA Luft	4000	1650	2400	9000	4520	1670	2750	10000	4920	1670	2750	11000	219	164	120	1000
S12R-PTA	1260	1008	1386	1109	Standard	TA Luft	4500	1650	2500	10500	5020	1670	2850	11200	*	*	*	*	264	198	145	1000
S12R-PTA2	1400	1120	1540	1232	Standard	TA Luft	5000	1800	2500	11000	5520	1820	2850	11700	*	*	*	*	293	220	161	1500
S12RY2-PTAW	1540	1232	1694	1355	Standard	TA Luft	5000	1800	2500	12000	5520	1820	2850	12700	*	*	*	*	307	230	169	1500
S16R-PTA	1730	1384	1903	1522	Standard	TA Luft	5500	2000	2600	13100	6000	3500	3150	15150	*	*	*	*	352	264	194	1500
S16R-PTA2	1900	1520	2090	1672	Standard	TA Luft	5500	2000	2600	12200	6000	3500	3150	15150	*	*	*	*	397	298	219	1500
S16R-PTAA2	2000	1600	2200	1760	Standard	TA Luft	5500	2000	2600	12950	6000	3500	3150	15150	*	*	*	*	408	306	224	1500

POWERS ACCORDING TO ISO 8528-1!