

SENTRY HPS HT 10-80kVA

Uninterruptible Power Supply

Quality power supply

Sentry HPS is an On-Line double conversion (VFI) UPS with filtered and stabilized sinusoidal output voltage. Sentry HPS is immune to the interferences on the electric power supply line as it has special input and output filters.

Maximum reliability and power availability

The digital control of the appliance considerably improves reliability, since a reduction in electronic components lowers the likelihood of breakdowns. Digital control is provided by the microprocessor that, in the HPS series, controls all the internal parameters, thus increasing reliability and performance. In parallel connections, digital control ensures balance of the currents, which generally change over time due to phenomena such as vibrations and temperature, between the UPS units and the exchange of information with no need for manual tuning. Sentry HPS has been designed so that it can be connected in parallel even after the installation of the first unit. The power availability can be increased thanks to various configurations available such as the parallel configuration, the Dual Bus function and the Dynamic Dual Bus system.

High Efficiency

If required, the unit can work in ECO mode to increase efficiency

up to 98% and consequently reduce energy dissipation and costs. In this operating mode the mains is the priority source and the load is switched over to the Inverter only when the mains characteristics exceed the preset limits.

UPS for Industrial loads

Sentry HPS with its strong overload capability, output galvanic isolation and low harmonic current distortion, is the ideal solution for industrial applications. Thanks to the high battery current, HPS Series is suitable to work with large battery banks as it can guarantee recharging in 10 hours as recommended by the battery manufacturer.

Operating flexibility

Sentry HPS is an uninterruptible power supply with On-Line double conversion technology that can also operate in Line Interactive mode (Economy mode for units over 100 kVA). All power ratings of the HPS series can also be used as Frequency Converters 50 to 60 Hz and vice versa.

Mimic panel

The mimic panel allows easy and intuitive operation of the UPS. It gives access to the most important parameters: status and alarms, control commands, input, output, battery measurements (power, current, voltage, frequency and temperature) and settings. The Sentry HPS diagnostics system



includes up to 128 alarms or messages allowing precise and detailed identification of any event.

Maximum battery care

Optimal battery management includes: - periodic battery test, - protection against deep discharge, - recharge temperature compensated.

Motor Generator friendly

Thanks to the range of different UPS versions and to the input filter solutions, Sentry HPS Series modules offer low harmonic distortion and high power factor at the input. This makes them ideal for use in conjunction with the Motor Generator at the input. On request, the HPS Series is provided with a 'Motor Generator kit' that will inhibit the battery recharging and/or synchronization with bypass.

Maximum safety for personnel

The back feed protection device prevents any voltage back feed in the upstream distribution board, thus ensuring the safety of the maintenance personnel.

Front access

Sentry HPS has frontal access

SENTRY HPS HT 10-80kVA

Uninterruptible Power Supply

for all power and electronic components, even in those configurations with internal batteries. This reduces the floor space required and consequently reduces the installation costs.

Advanced communication

Aros Watch&Save 3000 software displays the most important information such as the input and output voltage, the load applied, the remaining back-up time, etc., in the form of bar graphs. The software is able to provide information even in the event of a failure, in support of the fault diagnostics. The Watch&Save 3000 software can be used to program the automatic shutdown of all open systems in the event of a prolonged black out. Sentry HPS can also operate with a network agent for applications on LAN or WAN networks. The UPS contains the following hardware interfaces: - RS232 serial port, - Dry contacts, - EPO (Emergency Power Off) contact for UPS shutdown using the remote emergency button.

Remote Service Support

TELEGUARD is a remote troubleshooting system that can signal any kind of unexpected event in real time. Any fault is immediately signalled, 24 hours a day, 365 days a year, to the service control centre, which can take immediate action either remotely or on site. Plus, a report is provided periodically, detailing all the most important

events that have taken place during the monitored period.

Expandability

The units can be connected in parallel up to 8 units to increase power availability or redundancy. The single module or the system can be expanded any time to suit power requirements without influencing the initial investment. Thanks to the peculiarity of the 'Hot System Expansion' feature, the additional unit can be connected in parallel while the other units are on-line and supplying regular power to the load. The new UPS is on-line and will be set up automatically.

Dual Bus System

The Dual Bus System powers the priority loads from two independent sources. This configuration increases the redundancy and availability level of a multi-module configuration. Each bus may consist of a single module or up to 8 modules in parallel, kept in synchro by the UGS (UPS Group Synchroniser).

Dynamic Dual Bus System

Two independent systems set in Dual Bus Configuration can be merged together at any time for system expansion or maintenance.

This provides a lot of flexibility in your installation in case of maintenance or when it is necessary to change the redundancy level of both systems.

Applications

Servers, Local Area Network (LAN), Data centers, telecommunications, industrial equipment, electro-medical equipment.

SENTRY HPS HT 10-80kVA

Uninterruptible Power Supply

INPUT	HT 10	HT 15	HT 20	HT 30
Voltage	400 V three-phase + N			
Voltage tolerance	± 20%			
Accepted frequency	45-65 Hz			
Current distortion	<5% with harmonic filter			
Power factor	>0,9 with harmonic filter			
Input phases	3			
Soft start (Power Walk In)	0-100% in 10'			
BY PASS	HT 10	HT 15	HT 20	HT 30
Rated voltage	400 V three-phase + N			
Voltage tolerance	± 15% (selectable from ± 10% to ± 25% from front panel)			
Rated frequency	50/60 Hz			
Frequency tolerance	± 2% (selectable from ± 1% to ± 5% from front panel)			
By-pass	Static and manual for maintenance			
BATTERIES	HT 10	HT 15	HT 20	HT 30
Type	Maintenance-free sealed lead-acid			
Nominal battery voltage	430 V V			
Number of Pb elements	192			
Recharge current	0,2xC10 A			
Recharging voltage	Variable according to the temperature (-0,5 V x °C)			
OUTPUT	HT 10	HT 15	HT 20	HT 30
Rated power	10000 VA	15000 VA	20000 VA	30000 VA
Active power at cosφ 0,8	8 kW	12kW	16 kW	24 kW
Phases number	3 + N			
Waveform	Sinewave			
Rated voltage	380-400-415 V (selectable) three-phase + N			
Frequency	50 or 60 Hz			
Frequency stability	± 0,05% in battery operation, ± 2% in synchronism with mains (± 5% selectable)			
Dynamic stability	± 5%			
Static stability	± 1%			
Crest factor (I _{peak} /I _{rms})	3 : 1			
Rated current	14 A	22 A	29 A	43 A
Output phases	3			
Overload	110% for 300', 125% for 10', 150% for 1'			
SYSTEM	HT 10	HT 15	HT 20	HT 30
AC/AC efficiency	> 90%		> 91%	
Noise	54 dBA at 1 m		60 dBA at 1 m	
Operating temperature	0 + 40 °C			
Relative humidity	<95% non condensing			
Back-feed protection	Standard			
Protection degree	IP20			
Remote signals	Volt free contacts (mains power failure, UPS on bypass, end of discharge pre-alarm, output 12Vdc 80mA)			

SENTRY HPS HT 10-80kVA

Remote controls	EPO and bypass			
Colour	Light grey RAL 7035			
Standards	Safety: EN 62040-1-1 and directive 2006/95/EC; EMC: EN 62040-2 and directive 2004/108/EC; classification according to IEC 62040-3 (Voltage Frequency Independent) VFI-SS-111			
Technology	On-line double conversion			
Weight (kg)	From 210 to 480 Kg	From 220 to 490 Kg	From 230 to 500 Kg	From 282 to 552 Kg
Dimensions (WxDxH) mm	555x720x1200 mm			

DATA	HT 10	HT 15	HT 20	HT 30
Back up time at full load (min)		From 0 to 20 Min.		
Installation	Tower			
Configuration	Parallel Unit			

OPTIONS	HT 10	HT 15	HT 20	HT 30
Battery cabinets for longer runtimes	Yes			
Empty battery cabinets for longer runtimes	Yes			
Parallel kit	Yes			
Optional filters	Yes			
Isolation transformer module (WxDxH)	555x720x1200 mm / 145 kg	555x720x1200 mm / 165 kg	555x720x1200 mm / 190 kg	555x720x1200 mm / 215 kg
LCD-based remote control panel	Yes			
LED-based remote control panel	Yes			
Communication software 'professional' version	Yes			

OPTIONS	HT 10	HT 15	HT 20	HT 30
12Pulse Rectifier	X	X		
Antiharmonic filter	X	X	X	X
MultiCom 351	X	X	X	X
MultiCom 301	X	X	X	X
NetMan 101 Plus	X	X	X	X
Multi I/O	X	X	X	X
IRMS Multi-Switch	X	X	X	X
AS/400 interface kit	X	X	X	X
UPS remote contacts expander	X	X	X	X
UGS - UPS Group Synchronizer	X	X	X	X
PSJ - Power System Joiner	X	X	X	X
MultiCom 401	X	X	X	X

SENTRY HPS HT 10-80kVA

INPUT	HT 40	HT 60	HT 80
Voltage	400 V three-phase + N		
Voltage tolerance	± 20%		
Accepted frequency	45÷65 Hz		
Current distortion	<5% with harmonic filter	<5% with harmonic filter	5<% with harmonic filter
Power factor	>0,9 with harmonic filter		
Input phases	3		
Soft start (Power Walk In)	0-100% in 10'		
BY PASS	HT 40	HT 60	HT 80
Rated voltage	400 V three-phase + N		
Voltage tolerance	± 15% (selectable from ± 10% to ± 25% from front panel)		
Rated frequency	50/60 Hz		
Frequency tolerance	± 2% (selectable from ± 1% to ± 5% from front panel)		
By-pass	Static and manual for maintenance		
BATTERIES	HT 40	HT 60	HT 80
Type	Maintenance-free sealed lead-acid		
Nominal battery voltage	430 V V		
Number of Pb elements	192		
Recharge current	0,2x C10 A	35 A A	
Recharging voltage	Variable according to the temperature (-0,5 V x °C)		
OUTPUT	HT 40	HT 60	HT 80
Rated power	40000 VA	60000 VA	80000 VA
Active power at cosφ 0,8	32 kW	48 kW	64 kW
Phases number	3 + N		
Waveform	Sinewave		
Rated voltage	380-400-415 V (selectable) three-phase + N		
Frequency	50 or 60 Hz		
Frequency stability	± 0,05% in battery operation, ± 2% in synchronism with mains (± 5% selectable)		
Dynamic stability	± 5%		
Static stability	± 1%		
Crest factor (I _{peak} /I _{rms})	3 : 1		
Rated current	58 A	87 A	115 A
Output phases	3		
Overload	110% for 300', 125% for 10', 150% for 1'		
SYSTEM	HT 40	HT 60	HT 80
AC/AC efficiency	> 92%	>92%	
Noise	60 dBA at 1 m	62 dBA at 1 m	
Operating temperature	0 + 40 °C		
Relative humidity	<95% non condensing		
Back-feed protection	Standard		
Protection degree	IP20		
Remote signals	Volt free contacts (mains power failure, UPS on bypass, end of discharge pre-alarm, output 12Vdc 80mA)		

SENTRY HPS HT 10-80kVA

Remote controls	EPO and bypass		
Colour	Light grey RAL 7035		
Standards	Safety: EN 62040-1-1 and directive 2006/95/EC; EMC: EN 62040-2 and directive 2004/108/EC; classification according to IEC 62040-3 (Voltage Frequency Independent) VFI-SS-111		
Technology	On-line double conversion		
Weight (kg)	330 Kg	450 (6p) 600 (12p) Kg	555 (6p) 780 (12p) Kg
Dimensions (WxDxH) mm	555x720x1200 mm	800x740x1400 (6p) 1070x740x1400 (12p) mm	

DATA	HT 40	HT 60	HT 80
Installation	Tower		
Configuration	Parallel Unit		

OPTIONS	HT 40	HT 60	HT 80
Battery cabinets for longer runtimes	Yes		
Empty battery cabinets for longer runtimes	Yes		
Parallel kit	Yes		
Optional filters	Yes		
Isolation transformer module (WxDxH)	555x720x1200 mm / 260 kg	640x740x1400 mm / 380 kg	640x740x1400 mm / 430 kg
LCD-based remote control panel	Yes		
LED-based remote control panel	Yes		
Communication software 'professional' version	Yes		

OPTIONS	HT 40	HT 60	HT 80
12Pulse Rectifier	X	X	
Antiharmonic filter	X	X	X
MultiCom 351	X	X	X
MultiCom 301	X	X	X
NetMan 101 Plus	X	X	X
Multi I/O	X	X	X
IRMS Multi-Switch	X	X	X
AS/400 interface kit	X	X	X
UPS remote contacts expander	X	X	X
UGS - UPS Group Synchronizer	X	X	X
PSJ - Power System Joiner	X	X	X
MultiCom 401	X	X	X