



ELEKTRO AGREGATI - GENERATING SETS

MOTORJI PERKINS - ENGINES PERKINS

VODNO HLAJENI MOTORJI - WATER COOLED ENGINES

50Hz / 1500 o/min - 230/400V

Engine type	Prime Power		Stand-by Power		DIESEL motor		Overall dimensions												Fuel			
	kVA	kW	kVA	kW	Electronic regulation	Certifikat Emisij	PM1-Open version				PM2-Water-proof canopy				PM3-Super silent canopy				Consumption			Tank
							L(mm)	W(mm)	H(mm)	M(kg)	L(mm)	W(mm)	H(mm)	M(kg)	L(mm)	W(mm)	H(mm)	M(kg)	100% (l/h)	75% (l/h)	50% (l/h)	(liter)
403C-11 G	9,1	7	10	8	Optional	Stage 2	1500	1000	1400	600	1520	1020	1700	800	2320	1020	1750	900	2,6	2,0	1,5	30
403C-15 G	13,3	11	15	12	Optional	Stage 2	1500	1000	1400	650	1520	1020	1700	850	2320	1020	1750	950	3,7	2,8	2,1	40
404C-22 G	20	16	22	18	Optional	Stage 2	1800	1100	1400	735	1820	1120	1700	935	2620	1120	1750	1035	5,4	4,0	2,9	50
1103A-33 G1	30	24	33	26	Optional	Stage 2	1800	1100	1400	900	1820	1120	1700	1200	2620	1120	1750	1300	7,1	5,4	3,9	70
1103A-33 TG1	42	34	46	37	Optional	Stage 2	1800	1100	1400	950	1820	1120	1700	1250	2620	1120	1750	1350	10,7	8,2	5,7	100
1103A-33 TG2	60	48	66	53	Optional	Stage 2	1800	1100	1400	1050	1820	1120	1700	1350	2620	1120	1750	1450	13,9	10,4	7,2	150
1104A-44 TG2	80	64	88	70	Optional	Stage 2	2500	1200	1600	1150	2520	1220	1900	1450	3320	1220	1950	1550	18,7	14,0	9,7	160
1104C-44 TAG2	100	80	110	88	Standard	Stage 2	2500	1200	1600	1250	2520	1220	1900	1550	3320	1220	1950	1650	22,6	17,1	11,2	200
1006 TAG	132	106	145	116	Standard	Stage 2	2500	1200	1600	2000	2520	1220	1900	2300	3320	1220	1950	2400	31,5	24,1	16,5	300
1006 TAG2	150	120	165	132	Standard	Stage 2	2500	1200	1600	2050	2520	1220	1900	2350	3320	1220	1950	2450	41,0	31,0	20,0	350
1106C-E66 TAG4	180	144	198	158	Standard	Stage 2	2500	1200	1600	2350	2520	1220	1900	2650	3320	1220	1950	2750	40,2	31,0	20,5	350
1306C-E 87 TAG3	208	166	229	183	Standard	Stage 2	3000	1400	2000	2500	3020	1420	2300	2800	3820	1420	2350	2900	45,1	35,0	24,0	400
1306C-E 87 TAG4	228	182	251	201	Standard	Stage 2	3000	1400	2000	2500	3020	1420	2300	2800	3820	1420	2350	2900	48,1	37,5	26,0	400
1306C-E 87 TAG6	250	200	275	220	Standard	Stage 2	3000	1400	2000	2500	3020	1420	2300	2800	3820	1420	2350	2900	55,0	42,0	28,7	500
2306C-E 14 TAG2	350	280	385	308	Standard	Stage 2	3000	1400	2000	2600	3020	1420	2300	3100	3820	1420	2350	3300	75	57	40	650
2306C-E 14 TAG3	400	320	440	352	Standard	Stage 2	3000	1400	2000	4100	3020	1420	2300	4600	3820	1420	2350	4800	86	64	44	700
2506A-E 15 TAG1	455	364	501	400	Standard	Stage 2	3000	1400	2000	4800	3020	1420	2300	5300	3820	1420	2350	5500	99	73	51	800
2506A-E 15 TAG2	500	400	550	440	Standard	Stage 2	3000	1400	2000	4850	3020	1420	2300	5350	3820	1420	2350	5550	106	81	55	900
2806A-E 18 TAG1A	600	480	660	528	Standard	Stage 2	3500	1500	2100	5400	3520	1520	2400	5900	4320	1520	2450	6100	129	96	63	1000
2806C-E 18 TAG2	650	520	715	572	Standard	Stage 2	3500	1500	2100	5300	3520	1520	2400	5800	4320	1520	2450	6000	132	97	66	1000
4006 23 TAG2	730	584	803	642	Standard	Stage 2	3500	1500	2100	6000	3520	1520	2400	6800	4320	1520	2450	7000	152	113	75	1000
4006 23 TAG3	800	640	880	704	Standard	Stage 2	4000	1700	2100	6000	4020	1720	2400	6800	4820	1720	2450	7000	167	126	84	1000
4008 TAG2A	1035	828	1139	911	Standard	Stage 2	4500	1800	2150	7800	4520	1820	2450	8600	*	*	*	*	213	160	111	1500
4012 46TWG2A	1250	1000	1375	1100	Standard	Stage 2	5500	2000	2500	9600	5520	2020	2800	10600	*	*	*	*	264	198	137	1500
4012 46TAG2A	1500	1200	1650	1320	Standard	Stage 2	5500	2000	2500	10500	5520	2020	2800	11500	*	*	*	*	300	225	156	1500
4012 46TAG3A	1750	1400	1925	1540	Standard	Stage 2	6000	2000	2700	14500	6020	2020	3000	15500	*	*	*	*	381	286	198	1500
4016 TAG2A	2050	1640	2255	1804	Standard	Stage 2	6000	2000	2700	15000	6020	2020	3000	16000	*	*	*	*	420	315	218	1500

POWERS ACCORDING TO ISO 8528-1!